


U.S. Serial No. 10/786,372
Attorney Docket No. 85588RLO

Amendments to the Claims

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Original) An electroluminescent device, comprising:
 - a) a spaced-apart anode and cathode; and
 - b) an organic layer disposed between the spaced-apart anode and cathode and including a polymer having arylamine repeating unit moiety represented by formula





wherein:





Ar, Ar₁, Ar₂, Ar₃, and Ar₄ are each individually aryl group of from 6 to 60 carbon atoms; or a heteroaryl group of from 4 to 60 carbons, or combinations thereof; or Ar₁ and Ar₂, Ar₃ and Ar₄, Ar₁ and Ar₄, Ar₂ and Ar₄ are connected through a chemical bond; and

X is a conjugated group having 2 to 60 carbon atoms.

2. (Original) The electroluminescent device of claim 1 wherein Ar₁ and Ar₂, Ar₃ and Ar₄, Ar₁ and Ar₄, Ar₂ and Ar₄ are connected by a chemical bond to form a group having $\overset{\text{Ar}_1}{\text{N}} - \text{Ar}_2$, $\overset{\text{Ar}_3}{\text{N}} - \text{Ar}_4$, $\overset{\text{Ar}_1}{\text{N}} - \text{Ar}_4$, or $\overset{\text{Ar}_2}{\text{N}} - \text{Ar}_4$ that includes the following carbazole and carbazole derivatives:




U.S. Serial No. 10/786,372
Attorney Docket No. 85588RLO



3. (Original) The electroluminescent device of claim 1 wherein X includes a plurality of groups.

4. (Original) The electroluminescent device of claim 1 wherein the organic layer is an emissive layer or a hole injection layer or both.

5. (Original) An electroluminescent device which includes an anode, a cathode, and a polymer disposed between the spaced-apart anode and cathode, the polymer being doped with one or more fluorescent dyes, phosphorescent dopants, or other light emitting material, the polymer including arylamine moiety has the repeating unit represented by formula



wherein:

Ar, Ar₁, Ar₂, Ar₃, and Ar₄ are each individually aryl group of from 6 to 60 carbon atoms; or a heteroaryl group of from 4 to 60 carbons, or combinations


U.S. Serial No. 10/786.372
Attorney Docket No. 85588RLO

thereof; or Ar₁ and Ar₂, Ar₃ and Ar₄, Ar₁ and Ar₄, Ar₂ and Ar₄ are connected through a chemical bond; and

X is a conjugated group of from 2 to 60 carbon atoms.

6. (Original) A method of making an electroluminescent device, comprising:

- a) providing an anode and cathode; and
- b) depositing an organic layer between the spaced-apart anode and cathode and including a polymer having arylamine moiety has the repeating unit represented formula



wherein:

Ar, Ar₁, Ar₂, Ar₃, and Ar₄ are each individually aryl group of from 6 to 60 carbon atoms; or a heteroaryl group of from 4 to 60 carbons, or combinations thereof; or Ar₁ and Ar₂, Ar₃ and Ar₄, Ar₁ and Ar₄, Ar₂ and Ar₄ are connected through a chemical bond; and

X is a conjugated group of from 2 to 60 carbon atoms.

7. (Original) The electroluminescent device of claim 6 wherein the organic layer is an emissive layer or a hole injection layer or both.

8. (New) The electroluminescent device of claim 1 wherein Ar, Ar₁, Ar₂, Ar₃, and Ar₄ are each phenyl.

9. (New) The electroluminescent device of claim 5 wherein Ar, Ar₁, Ar₂, Ar₃, and Ar₄ are each phenyl.

10. (New) The method of claim 6 wherein Ar, Ar₁, Ar₂, Ar₃, and Ar₄ are each phenyl.